



| | CHAMBER WIDTH | CHAMBER SPACING | CENTER TO CENTER | CHAMBER HEIGHT | MAX END CAP CONNECTION |
|-----|----------------|-------------------------------|-----------------------------------|----------------|------------------------|
| S29 | 59" (1499mm) | 6.0" (150mm) *7.5" (190mm) | 65.0" (1651mm) *66.5" (1690mm) | 36" (914mm) | 32" (813mm) |
| S22 | 55" (1397mm) | 6.0" (150mm) | 61.0" (1549mm) | 35" (889mm) | 30" (762mm) |
| C10 | 39.7" (1008mm) | 6.0" (150mm) | 45.7" (1161mm) | 25" (635mm) | 20" (508mm) |
| M6 | 33.6" (853mm) | 6.0" (150mm) | 39.6" (1006mm) | 17.5" (445mm) | 14" (356mm) |

*7.5" (190mm) SPACING OF DISTRIBUTION ROWS IS REQUIRED ONLY WHEN A PERPENDICULAR MAIN HEADER ROW IS USED. IF AN INLINE MAIN HEADER ROW IS USED, THEN MIN SPACING CAN BE 6" (150mm)

CONCEPTUAL PLAN DISCLAIMER
 THIS GENERIC DETAIL DOES NOT ENCOMPASS THE SIZING, FIT, AND APPLICABILITY OF THE TRITON CHAMBER SYSTEM FOR THIS SPECIFIC PROJECT. IT IS THE ULTIMATE RESPONSIBILITY OF THE DESIGN ENGINEER TO ASSURE THAT THE STORMWATER SYSTEM DESIGN IS IN FULL COMPLIANCE WITH ALL APPLICABLE LAWS AND REGULATIONS. TRITON PRODUCTS MUST BE DESIGNED AND INSTALLED IN ACCORDANCE WITH TRITON'S MINIMUM REQUIREMENTS. TRITON STORMWATER SOLUTIONS DOES NOT APPROVE PLANS, SIZING, OR SYSTEM DESIGNS. THE DESIGN ENGINEER IS RESPONSIBLE FOR ALL DESIGN DECISIONS.



7600 EAST GRAND RIVER, STE.195
 BRIGHTON, MI 48114
 PHONE: (810) 222-7652 • FAX: (810) 222-1769
 WWW.TRITONSW.COM

TRITON CROSS SECTION

WITH SAND FILTRATION LAYER - LOW PROFILE OPTION

TRITON - STANDARD DETAILS

REVISED:
 06-22-16 JWM